

| | |
|---|--|
| Client: <i>Sea Tank Chartering AS.</i> | Industry: <i>Marine</i> |
| Vessel: <i>Chemical Tanker</i> | Date: <i>April 2016</i> |
| Location: <i>Poland</i> | Products: <i>RE 500P & RW 500</i> |

Overview

The chemical cargo tanks onboard the chemical tanker were suffering from severe corrosion damage and had to be refurbished.

Challenge

The client required a new coating system with the capability of handling extremely aggressive chemicals operating at high temperatures. There was also a short time frame for project completion due to the quantity of tanks required to be refurbished during the dry-docking programme.

Solution

For areas where a full refurbishment was required, the cargo tanks were grit blasted to Sa 2½ standard. Furthermore, areas which required to be spot repaired were mechanically prepared to St 3 standard. This was followed by one primer coat of **solvent-free**, Novolac epoxy **Epo-chem™ RE 500P**. To complete the coating system, one stripe coat and two topcoats of **solvent-free**, glassflake Novolac epoxy **Epo-chem™ RW 500** was applied.

Outcome

The project was successfully completed within the given time frame. The fast post curing of the **Chemco** system was considered a major time and cost saving advantage.

Benefits

- Solvent-free
- No grit blasting requirements for spot repair work
- Excellent chemical and high temperature resistance
- Reduced contract duration and downtime
- Ease of decontamination (no cargo contamination)

Continued overleaf

1



2



3



Photographs:

- Nos. 1-2 Original Conditions
- No. 3 After Grit Blasting

4



5



6



7



8



9



Photographs:

- No. 4 After Mechanical Preparation
- No. 5 Primer Spot Applied
- Nos. 6-7 Applying Topcoat on Primed Surface
- Nos. 8-9 Completed Application

East Shawhead Industrial Estate
Coatbridge ML5 4XD
Scotland United Kingdom
Tel: +44 (0) 1236 606060
Fax: +44 (0) 1236 606070
Email: sales@chemcoint.com
Web Site: www.chemcoint.com